

# Tachometer



Type	isi36	TA134	TA200	TA201	TA202
	<b>isiLine</b>	<b>ProLine</b>	<b>ProLine</b>	<b>ProLine</b>	<b>ProLine</b>
<b>Supply voltage</b>	Internal lithium battery	24, 48, 115, 230 VAC, 12...30 VDC	24, 48, 115, 230 VAC, 24 VDC	24, 48, 115, 230 VAC, 24 VDC	24, 48, 115, 230 VAC, 24 VDC
<b>Sensor supply</b>	--	12...26 VDC, max. 60 mA	12...26 VDC, max. 100 mA	12...26 VDC, max. 100 mA	12...26 VDC, max. 100 mA
<b>Outputs</b>	--	Relay or electric	--	--	Relay or electric
<b>Counting frequency</b>	30 Hz, 7 kHz, 12 kHz	25 Hz, 40 kHz	25 Hz, 40 kHz	25 Hz, 10 / 40 kHz	25 Hz, 10 / 40 kHz
<b>Signal inputs</b>	NPN, PNP	NPN, PNP, AC	NPN, PNP	NPN, PNP	NPN, PNP
<b>Display</b>	LCD, 8-digit	LCD, 6-digit	LED, 6-digit	LED, 6-digit	LED, 6-digit
<b>Interface</b>	--	RS485	--	--	RS232 / 422 / 485
<b>Power consumption</b>	--	5 VA, 4 W	6 VA, 4 W	6 VA, 4 W	7 VA, 5 W
<b>Front dimensions</b>	48 x 24 mm	48 x 48 mm	96 x 48 mm	96 x 48 mm	96 x 48 mm
<b>Particularities</b>	Optional: Display backlight illumination	Background illumination	--	Calculation function	Calc. funct. and limit value